



2010 SUGGESTED RETAIL PRICES

Revised Date: 16 March 2010

NOTES:

- * These are Manufacturer's Suggested Retail (MSRP) or End-User Prices.
- * Morningstar controllers are only sold through authorized Morningstar distributors and dealers located throughout the world.
- * Please contact Morningstar or your Distributor or Dealer for price discounts.
- * All pricing in U.S. Dollars
- * 5-year warranty period for controllers. 2-year warranty period for SHS and Inverter products.

Part Number:	Description:	RETAIL PRICE *
INVERTERS		
SI-300-115V-UL	SureSine-300 watt (115 Volt, 60hz)	310
SI-300-220V	SureSine-300 watt (220 Volt, 50hz)	308
MPPT CONTROLLERS <i>MPPT: Maximum Power Point Tracking</i>		
<i>TriStar MPPT</i>		
TS-MPPT-45	TriStar MPPT 45 amp (12, 24, or 48 Volts DC)	531
TS-MPPT-60	TriStar MPPT 60 amp (12, 24, or 48 Volts DC)	669
<i>SunSaver MPPT</i>		
SS-MPPT-15L	SunSaver MPPT 15 amp (12/24 Volts DC)	278
PWM CONTROLLERS <i>PWM: Pulse Width Modulation</i>		
<i>TriStar</i>		
TS-45	TriStar-45 amp (12/24/48 Volt)	175
TS-60	TriStar-60 amp (12/24/48 Volt)	226
<i>ProStar</i>		
PS-15	ProStar-15 amp (12/24 Volt)	115
PS-15M	ProStar-15 amp with Meter (12/24 Volt)	184
PS-15M-48V	ProStar-15 amp with Meter (48 Volt)	229
PS-15M-48V-PG	ProStar-15 amp with Meter (48 Volt, Positive Ground)	246
PS-30	ProStar-30 amp (12/24 Volt)	157
PS-30M	ProStar-30 amp with Meter (12/24 Volt)	226
PS-30M-PG	ProStar-30 amp with Meter (12/24 Volt, Positive Ground)	243
<i>SunSaver</i> L = LVD, Low Voltage Disconnect		
SS-6-12V	SunSaver-6 amp (12 Volt)	50
SS-6L-12V	SunSaver-6 amp with LVD (12 Volt)	61
SS-10-12V	SunSaver-10 amp (12 Volt)	57
SS-10L-12V	SunSaver-10 amp with LVD (12 Volt)	73
SS-10L-24V	SunSaver-10 amp with LVD (24 Volt)	79
SS-20L-12V	SunSaver-20 amp with LVD (12 Volt)	99
SS-20L-24V	SunSaver-20 amp with LVD (24 Volt)	105
<i>SunSaver Duo</i>		
SSD-25	SunSaver-Duo 25 amp (12 Volts DC)	110
SSD-25RM	SunSaver-Duo 25 amp (12 Volts DC) with Meter (Kit)	188

Operator Manuals, Technical Notes and Specifications for all Morningstar Products are available at: www.morningstarcorp.com

8 Pheasant Run, Newtown PA 18940 USA Tel +1-215-321-4457 Fax +1-215-321-4458

Web: www.morningstarcorp.com



2010 SUGGESTED RETAIL PRICES

Revised Date: 16 March 2010

Part Number:	Description:	RETAIL PRICE *
PWM CONTROLLERS		<i>PWM: Pulse Width Modulation</i>
<i>SunKeeper</i>		
SK-6	SunKeeper-6 amp (12 Volt)	63
SK-12	SunKeeper-12 amp (12 Volt)	89
<i>SunLight</i> L = LVD, Low Voltage Disconnect		
SL-10L-12V	SunLight-10 amp with LVD (12 Volt)	111
SL-10L-24V	SunLight-10 amp with LVD (24 Volt)	119
SL-20L-12V	SunLight-20 amp with LVD (12 Volt)	145
<i>SunGuard</i>		
SG-4	SunGuard-4 amp (12 Volt)	31
<i>SHS Controller</i> SPECIAL NOTE: SHS Unit is Not Available for Use and Resale in the USA and Canada		
SHS-6	SHS-6 amp with LVD (12 Volt)	30
SHS-10	SHS-10 amp with LVD (12 Volt)	40
ACCESSORIES		
TS-M	Replaced by TS-M-2, SEE BELOW	
TS-RM	Replaced by TS-RM-2, SEE BELOW	
TS-M-2	TriStar Digital Meter (for TS and TS-MPPT)	104
TS-RM-2	TriStar Remote Digital Meter (for TS and TS-MPPT)	138
RM-1	Remote Meter	97
RD-1	Relay Driver	169
HUB-1	MeterHub	115
RTS	Remote Temperature Sensor	32
MSC	PC Meterbus Adapter	39
RSC-1	EIA-485/RS-232 Communications Adapter	69
DIN-1	DIN Rail Mounting Clips	1
ACCESSORY NOTES:		
TS-M-2: TriStar Digital Meter for use with TS and TS-MPPT.		
TS-RM-2: TriStar Remote Digital Meter for use with TS and TS-MPPT.		
RM-1: Remote Meter may be used with SunSaver Duo, SunSaver MPPT or SureSine Inverter.		
RD-1: Relay Driver may be used with TriStar or TS-MPPT.		
HUB-1: MeterHub may be used with SS-MPPT, TriStar, TS-MPPT, TS-M-2, TS-RM-2 or Relay Driver (RD-1).		
RTS: Remote Temperature Sensor may be used with ProStar, TriStar, SunSaver Duo, SS-MPPT, or TS-MPPT (RTS is included with TS-MPPT).		
MSC: PC Meterbus Adapter may be used with SunSaver Duo, SS-MPPT or SureSine Inverter.		
RSC-1: May be used with any device equipped with a RS-232 port. (RSC-1 converts RS-232 port to EIA-485 serial connector)		
DIN-1: May be used with SunLight, SunSaver, SunSaver Duo or SS-MPPT controllers; 2 mounting clips required per controller.		

Operator Manuals, Technical Notes and Specifications for all Morningstar Products are available at: www.morningstarcorp.com

8 Pheasant Run, Newtown PA 18940 USA Tel +1-215-321-4457 Fax +1-215-321-4458
 Web: www.morningstarcorp.com